

JET-216AP



200W ATX Power Supply with PFC for 1U Chassis



SPECIFICATION

Input Voltage : 100V~240V AC full range

Input Frequency : 47~63Hz

Input Current : 5A max. for 100V~240V AC

Inrush Current (Cold) : Full load at 115/230V AC
Cold start at 25°C

Efficiency : Min. 65% at full load

Operation Temperature : 0°C~50°C

Humidity : 0% to 85% non-condensing

Over Voltage Protection : +5V to 6.5V at +5V
13.5V to 14.5V at +12V

Over Power Protection : +3.3V DC : 4.5V DC max
+5V DC : 7.0V DC max

+12V DC : 15.6V DC max
Short Circuit Protection : +3.3V, +5V, +12V rails
to return

Hold Up Time : 16ms

Dimension (HxWxD) : 41 x 97.1 x 215mm

OUTPUT CHARACTERISTICS

Output Voltage	Load		Tolerance	Ripple & Noise
	Min.	Max.		
+3.3V	0.1A	12.5A	±5%	100mV
+5V	2.0A	22.0A	±5%	100mV
+12V	0.5A	8.0A	±5%	200mV
-5V	0A	0.1A	±10%	100mV
-12V	0A	0.3A	±10%	200mV
+5Vsb	0A	1.5A	±5%	100mV

Remark : +5V +3.3V & +12V total
power 190W max.