



Features

- Supports Socket 370 based Intel® Pentium® III / Celeron® Processor
- C&T 69000 LCD controller supports 36-bit TFT Panels
- Supports DiskOnChip® up to 1GB
- High Drive design to enhance ISA driving capacity



Specifications

System

- CPU: Socket 370 based Pentium® III Processor / Celeron® Processor (.18 μ / .25 μ) up to 1.1 GHz (with system bus frequencies of 66/100MHz)
- System Memory: SDRAM DIMM x 3, Max 768MB
- Chipset: Intel® 440BX
- I/O Chipset: Winbond W83977TF. Fully 16-bit I/O decoded
- BIOS: Award 256KB FLASH ROM
- SSD: Supports DiskOnChip® up to 1GB
- Watchdog Timer: Can generate a system reset, IRQ15 or NMI
- Expansion Interface: PICMG 2.0
- Battery: Lithium battery
- DMA: 7 DMA channels (8237 equivalent)
- Interrupt: 15 interrupt levels (8259 equivalent)
- H/W status monitoring: Winbond W83781D H/W status monitoring IC supports power supply voltages, fan speed control and temperature monitoring
- Power supply voltage: +5V (4.75V to 5.25V), +12V(11.4V to 12.6V), ATX/AT
- Size/ Weight: 13.3" (L) x 4.8" (W) (338 mm x 122 mm), 1.2lb.(0.5Kg)
- Operating temperature: 32°F to 140°F (0°C to 60°C)

I/O

- MIO: IDE (UDMA33) x 2, FDD x 1, KB+Mouse x 1, RS-232 x 1, RS-232/422/485 x 1, Parallel x1
- IrDA: One IrDA Tx/Rx header
- USB: One 5x2 pin header supports 2 USB 1.1 ports

Display

- Chip: C&T 69000
- Memory Size: Built-in 2MB SDRAM
- Resolution: Up to 1024 x 768 @ 16bpp colors
- LCD Interface: 36-bit TFT/DSTN/MONO LCD panel

Packing List

- IDE cable
- FDD cable
- COM Port cable kit (1 parallel, 1 serial) 9657590000
- KB/Mouse cable 1700060192
- USB cable 1709100201
- Quick Installation Guide
- Utility CD