



1585A Paired - CCTV Fixed and PTZ Applications

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Color Code Chart : No. 8 for DataTwist Cables (Modified Western Electric).pdf</p>
--	---

Description:

24 AWG solid bare copper conductors, FEP insulation, Flamarrest® jacket with ripcord, sequential footage marking every two feet.

SUITABLE APPLICATIONS:

Suitable Applications	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422
-----------------------	--

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	FRPO/FEP - Flame Retardant Polyolefin/Fluorinated Ethylene Propylene
---------------------	--

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material Trade Name	Flamarrest®
Outer Jacket Material	LS PVC - Low Smoke Polyvinyl Chloride
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:



1585A Paired - CCTV Fixed and PTZ Applications

Overall Nominal Diameter	.195 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
Bulk Cable Weight	24.4 lbs/1000 ft.
Max. Recommended Pulling Tension	35 lbs.
Min. Bend Radius (Install)	0.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMP, UL444
CEC/C(UL) Specification	CMP
IEC Specification	11801 Category 5
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005
TIA/EIA Specification	568-B.2 Category 5e
Other Specification	NEMA WC-63.1 Category 5e, ETL Verified to Category 5e

FLAME TEST:

UL Flame Test	NFPA 262
CSA Flame Test	FT4, FT6

PLENUM/NON-PLENUM:

Plenum (Y/N)	Y
Non-Plenum Number	1583A, 1583R

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	330 pF/100 m
Nominal Velocity of Propagation	72 %
Maximum Delay (ns/100 m)	538 @ 100MHz ns/100 m
Maximum Delay Skew (ns/100m)	45 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9.38 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	3 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :	
-------------------------------------	--

1585A Paired - CCTV Fixed and PTZ Applications

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	65.3	62.3	63.0	60.0	20.0	23.0
4	4.1	56.3	53.3	51.0	49.0	23.0	23.0
8	5.8	51.8	48.8	46.0	43.0	24.5	24.5
10	6.5	50.3	47.3	43.0	41.0	25.0	25.0
16	8.2	47.3	44.3	39.0	36.0	25.0	25.0
20	9.3	45.8	42.8	36.5	33.5	25.0	25.0
25	10.4	44.3	41.3	33.9	30.9	24.3	24.3
31.25	11.7	42.9	39.9	31.0	28.0	23.6	23.6
62.5	17.0	38.4	35.4	22.0	19.0	21.5	21.5
100	22.0	35.3	32.3	14.0	11.0	20.1	20.1
155	28.1	32.5	29.5	4.4	1.4	15.8	
200	32.0	30.8	27.8	4.0	1.0	15.0	

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.8	60.8
4	100 ± 15	100 ± 15	51.7	48.7
8	100 ± 15	100 ± 15	45.7	42.7
10	100 ± 15	100 ± 15	43.8	40.8
16	100 ± 15	100 ± 15	39.7	36.7
20	100 ± 15	100 ± 15	37.7	34.7
25	100 ± 15	100 ± 15	35.8	32.8
31.25	100 ± 15	100 ± 15	33.9	30.9
62.5	100 ± 15	100 ± 15	27.8	24.8
100	100 ± 15	100 ± 15	23.8	20.8
155	100 ± 25	100 ± 15	19.9	16.9
200	100 ± 25	100 ± 15	17.7	14.7

NOTES:

Notes

Jacket sequentially marked at 2 ft. intervals. Thrid party verified to TIA/EIA-568-B.2, Category 5e.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1585A 0021000	4 PR #24 FEP FLMRST	1000	24	RED	C
1585A 002U1000	4 PR #24 FEP FLMRST	U1000	23	RED	
1585A 0031000	4 PR #24 FEP FLMRST	1000	24	ORANGE	C
1585A 003U1000	4 PR #24 FEP FLMRST	U1000	23	ORANGE	

1585A Paired - CCTV Fixed and PTZ Applications

1585A 0041000	4 PR #24 FEP FLMRST	1000	24	YELLOW	C
1585A 004U1000	4 PR #24 FEP FLMRST	U1000	23	YELLOW	
1585A 0051000	4 PR #24 FEP FLMRST	1000	24	GREEN, DARK	C
1585A 005U1000	4 PR #24 FEP FLMRST	U1000	23	GREEN, DARK	
1585A 0081000	4 PR #24 FEP FLMRST	1000	24	GRAY	C
1585A 008U1000	4 PR #24 FEP FLMRST	U1000	23	GRAY	
1585A 0091000	4 PR #24 FEP FLMRST	1000	24	WHITE	C
1585A 009U1000	4 PR #24 FEP FLMRST	U1000	23	WHITE	
1585A 0101000	4 PR #24 FEP FLMRST	1000	24	BLACK	C
1585A 010U1000	4 PR #24 FEP FLMRST	U1000	23	BLACK	
1585A 0121000	4 PR #24 FEP FLMRST	1000	24	PINK	C
1585A 012U1000	4 PR #24 FEP FLMRST	U1000	23	PINK	
1585A 8771000	4 PR #24 FEP FLMRST	1000	24	NATURAL	C
1585A 8773000	4 PR #24 FEP FLMRST	3000	69	NATURAL	C
1585A 877U1000	4 PR #24 FEP FLMRST	U1000	23	NATURAL	
1585A D151000	4 PR #24 FEP FLMRST	1000	24	BLUE	C
1585A D153000	4 PR #24 FEP FLMRST	3000	69	BLUE	C
1585A D15U1000	4 PR #24 FEP FLMRST	U1000	23	BLUE	

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 12-15-2005

1585A Paired - CCTV Fixed and PTZ Applications

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.