



KVM-8P

19" 1U High, Half-size Rackmount 8-port KVM Switch

KVM Switch



Features

- ◆ Slimmest 19" 1U high, half-size rackmount 8-port KVM switch design
- ◆ Supports MS Intellimouse, Intellimouse Explorer, Logitech Net Mouse or the other fully compatible MS mouse
- ◆ Provides Console PS/2 to PC serial mouse conversion
- ◆ Supports DOS, Win3.X, Win95/98/98SE/2K/ME/XP, WinNT, Netware, SCO UNIX, HP UNIX, Linux
- ◆ Hot plug - add PCs or remove connected PCs for maintenance without powering down the KVM switch or PCs
- ◆ Very high video quality - up to 1920 x 1440, bandwidth: 200MHz
- ◆ No software required - easy PC selection via On Screen Display manual, push buttons, hot keys
- ◆ Supports eight characters password protection and search PC server name
- ◆ Auto scan mode for monitoring PCs and flexible scan time is 5~99 sec.
- ◆ Keyboard status restored when switching PCs
- ◆ LED display for easy status monitoring
- ◆ Buzzer sound for switching port confirmation
- ◆ Using standard VGA, keyboard, mouse cable
- ◆ Built-in one extra daisy chain port and without wasting any PC port
- ◆ NO DIP switch setting needed and auto detect daisy chain bank

Specifications

PC Port

8

Console Port

1

PC/Console/Daisy Chain Port

15-pin CRT, PS/2 6-pin Mini DIN keyboard, PS/2 6-pin Mini DIN mouse

PC Selection

On Screen Display menu, hot key, push button

7 Segment LED

Bank LED x 1, PC port LED x 2

OSD Control

Yes

Scan Intervals

5~99 seconds

Keyboard Emulation

PS/2 6-pin Mini DIN

Mouse Emulation

PS/2 6-pin Mini DIN

Mouse Conversion

Console PS/2 to each PC port serial mouse

VGA Resolution

1920 x 1440

Bandwidth

200MHz

Daisy Chain Level

8 levels max.

PC Connection

120 max.

Housing/Size

Metal/19" 1U high, rackmount

Power Supply

DC 12V/1A or DC 9V/1A

Temperature

0~+40°C (operating); -20~+60°C (storage)

Humidity

0~95%; non-condensing

Dimensions (L x W x H)

41.0 x 16.5 x 4.4 cm

Ordering Guide

- ◆ **KVM-8P (by order)**
19" 1U High, Half-size Rackmount 8-port KVM Switch