



### PC-64T 6.4" TFT Panel PC

100% water-proof, IP-65,66, 67, NEMA-4,12  
Meet VESA-75 wall-mount and panel mount  
8mm aluminum bezel, rugged steel construction  
6.4" TFT, 640 x 480, 250 cd/m2, Resistive touch  
Low power 1Ghz CPU, 128/256/512M RAM  
32MB video share RAM, AGP 4x, Audio  
LAN, 2 x USB, 4 x COM, Support RS232/422/485  
Anti-vibration, anti-shock design  
20/40G anti-vibration slim HDD



### PPC-1510PT 15" Panel PC

100% water-proof front, IP-65,66, NEMA-4, 12  
Meet VESA-75,100 wall-mount and panel-mount  
10mm aluminum bezel, rugged steel construction  
15" TFT, 1024 x 768, 250 cd/m2, resistive touch  
Low power 1Ghz CPU, 128 - 512 SDRAM  
8MB video RAM, AGP 4x, Audio, Speakers  
LAN, 2 x USB 2.0, 4 x COM, Support RS232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-812T 8" TFT Panel PC

Meet VESA-75 wall-mount  
Rugged steel construction  
8" TFT, 640 x 480, 380 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-1511PT 15" Fanless Panel PC

Meet VESA-75,100 wall-mount  
Rugged steel construction  
15" TFT, 1024 x 768, 250 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-813T 8" TFT Panel PC

Meet VESA-75 wall-mount  
Rugged steel construction  
8" TFT, 640 x 480, 380 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design  
Card Reader



### PPC-1513PT 15" TFT Panel PC

Meet VESA-75,100 wall-mount  
Rugged steel construction  
15" TFT, 1024 x 768, 250 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-872T 8" TFT Panel PC

100% water-proof front, IP-65,66, NEMA-4, 12  
Meet VESA-75 wall-mount and panel-mount  
8mm aluminum bezel, rugged steel construction  
8" TFT, 640 x 480, 380 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-1514PT Intel P-4 Mobile Centrino CPU

Meet VESA-75,100 wall-mount  
Rugged steel construction  
15" TFT, 1024 x 768, 250 cd/m2, Analog touch  
Intel Pentium M CPU equivalent to Celeron 2.4 Ghz  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, Audio, Speakers  
2 x LAN, 6 x USB 2.0, 2 x COM, Support RS232 only  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-1072PT / 1072SVGA

100% water-proof front, IP-65,66, NEMA-4, 12  
Meet VESA-75,100 wall-mount and panel-mount  
10mm aluminum bezel, rugged steel construction  
10" TFT, 800 x 600, 280 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-1572PT Fanless 15" Panel PC

100% water-proof front, IP-65,66, NEMA-4, 12  
Meet VESA-75,100 wall-mount and panel-mount  
10mm aluminum bezel, rugged steel construction  
15" TFT, 1024 x 768, 250 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-129PT 12.1" Panel PC

100% water-proof front, IP-65,66, NEMA-4, 12  
Meet VESA-75,100 wall-mount and panel-mount  
10mm aluminum bezel, rugged steel construction  
12" TFT, 800 x 600, 250 cd/m2, resistive touch  
Low power 1Ghz CPU, 128 - 512 SDRAM  
8MB video RAM, AGP 4x, Audio, Speakers  
LAN, 2 x USB, 4 x COM, Support RS232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-1573PT 15" Panel PC

100% water-proof front, IP-65,66, NEMA-4, 12  
Meet VESA-75,100 wall-mount and panel-mount  
10mm aluminum bezel, rugged steel construction  
15" TFT, 1024 x 768, 250 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-1272PT 12.1" TFT Panel PC

100% water-proof front, IP-65,66, NEMA-4, 12  
Meet VESA-75,100 wall-mount and panel-mount  
10mm aluminum bezel, rugged steel construction  
12" TFT, 800 x 600, 250 cd/m2, Analog touch  
Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
2 x LAN, 4 x USB 2.0, 4 x COM, Support 232/422/485  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



### PPC-1574PT Intel P-4 Mobile Centrino CPU

100% water-proof front, IP-65,66, NEMA-4, 12  
Meet VESA-75,100 wall-mount and panel-mount  
10mm aluminum bezel, rugged steel construction  
15" TFT, 1024 x 768, 250 cd/m2, Analog touch  
Intel Pentium M CPU equivalent to Celeron 2.4 Ghz  
64MB video RAM, AGP 8x, Audio, Speakers  
2 x LAN, 6 x USB 2.0, 2 x COM, Support RS232 only  
20G / 40G slim anti-vibration HDD or DOM  
Anti-vibration, anti-shock design



**PPC-1575PT-400 ultra hi-bright Panel PC**  
 100% water-proof front, IP-65,66, NEMA-4, 12  
 Meet VESA-75,100 wall-mount and panel-mount  
 10mm aluminum bezel, rugged steel construction  
 15" TFT, 1024 x 768, 400 cd/m2, Analog touch  
 Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 2 x LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 20G / 40G slim anti-vibration HDD or DOM  
 Anti-vibration, anti-shock design

\* Out door readable display



**PPC-1872PT 18" Panel PC**  
 100% water-proof front, IP-65,66, NEMA-4, 12  
 Meet VESA-75,100 wall-mount and panel-mount  
 10mm aluminum bezel, rugged steel construction  
 18" TFT, 1280 x 1024, 250 cd/m2, Analog touch  
 Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 2 x LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 40G / 80G HDD or DOM  
 Anti-vibration, anti-shock design



**PPC-1576PT / 1576PT-VP (Vandal-proof)**  
 100% water-proof front, IP-65,66, NEMA-4, 12  
 Meet VESA-75,100 wall-mount and panel-mount  
 10mm aluminum bezel, rugged steel construction  
 15" TFT, 1024 x 768, 1600 cd/m2, Analog touch  
 Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 2 x LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 20G / 40G slim anti-vibration HDD or DOM  
 Anti-vibration, anti-shock design  
**Strike free / Cut free / Chemical liquid free**

\* Sun light readable display



**PPC-2012PT / PPC-2012PT-SXGA**  
 Meet VESA-75,100 wall-mount  
 Rugged steel construction  
 20" TFT, 800 x 600, 380 cd/m2, Analog touch  
 Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 2 x LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 40G / 80G HDD or DOM  
 Anti-vibration, anti-shock design  
**\* PPC-2012PT-SXGA: 1600 x 1200 resolution**



**PPC-1772PT 17" TFT Panel PC**  
 Meet VESA-75,100 wall-mount  
 Rugged steel construction  
 17" TFT, 1024 x 1024, 300 cd/m2, Analog touch  
 Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 2 x LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 40G / 80G HDD or DOM  
 Anti-vibration, anti-shock design



**PPC-2113P 21" Panel PC**  
 Meet VESA-75, 100 wall-mount  
 Rugged steel construction  
 21" TFT, 1024 x 768, 450 cd/m2, Analog touch  
 Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 2 x LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 40G / 80G HDD or DOM  
 Anti-vibration, anti-shock design



**PPC-1773PT 17" TFT Panel PC**  
 Meet VESA-75,100 wall-mount  
 Rugged steel construction  
 17" TFT, 1280 x 1024, 300 cd/m2, Analog touch  
 Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 2 x LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 40G / 80G HDD or DOM  
 Anti-vibration, anti-shock design



**PPC-2311P 23" Panel PC**  
 Meet VESA-75 x 4 wall-mount  
 Rugged steel construction  
 23" TFT, 1280 x 768, 450 cd/m2, Analog touch  
 Low power 2.4Ghz CPU, 2GB DRAM(MAX)  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 40G / 80G HDD or DOM  
 Anti-vibration, anti-shock design



**PPC-1812PT 18" Panel PC**  
 Meet VESA-75,100 wall-mount  
 Rugged steel construction  
 18" TFT, 1280 x 1024, 200-250 cd/m2, touch  
 Low power 1Ghz CPU, 256 / 512M / 1GB DDR  
 64MB video RAM, AGP 8x, MPEG-II, Speakers  
 2 x LAN, 4 x USB 2.0, 4 x COM  
 Support RS422/485  
 40G / 80G HDD or DOM  
 Anti-vibration, anti-shock design



**PPC-3011PT 30" Panel PC**  
 Meet VESA-75 x 4 wall-mount  
 Rugged steel construction  
 30" TFT, 1280 x 768, 450 cd/m2, Analog touch  
 Low power 2.4Ghz CPU, 2GB DRAM(MAX)  
 64MB video RAM, AGP 8x, MPEG-II, Audio, Speakers  
 LAN, 4 x USB 2.0, 4 x COM, Support RS422/485  
 40G / 80G HDD or DOM  
 Anti-vibration, anti-shock design



MS-2500



MS-2600



MS-2700



MS-2800



MS-2900P-CF



MS-2900P-HD

## Mini PC Series

Model No.	Fanless	CPU	DDR RAM(Max)	AGP/VRAM/MPEG-II	PCI slot	DOM	CF/PCMCIA	COM	USB 2.0	LAN
MS-2500	YES	Low Power 1Ghz	1GB DRAM	8X ,64MB ,MPEG-II	X	O	YES/YES	4	4	2
MS-2600	YES	Low Power 1Ghz	1GB DRAM	8X ,64MB ,MPEG-II	O	O	NO/NO	4	4	2
MS-2700	YES	Low Power 1Ghz	1GB DRAM	8X ,64MB ,MPEG-II	X	O	NO/NO	4	4	2
MS-2800	NO	Low Power 1Ghz	1GB DRAM	8X ,64MB ,MPEG-II	X	O	YES/YES	4	4	2
MS-2900P-CF	YES/NO	Low Power 1Ghz	1GB DRAM	8X ,64MB ,MPEG-II	O	O	YES/NO	4	4	2
MS-2900P-HD	YES/NO	Low Power 1Ghz	1GB DRAM	8X ,64MB ,MPEG-II	O	O	NO/NO	4	4	2

\* Option: CF slot, PCI slot, GPS module