

HDF 6015 SERIES

DC FAN

Operating Temp. Range: -20~+60°C

Locked Rotor & Polarity Protected

Safety Standards: UL/CUR/TUV

Bearing : Dual Ball Bearing

Housing : Plastic with plastic impeller

Third Wire Alarm Available: (-01A) Locked Rotor Alarm

(-50A) Pulse Alarm



60 x 60 x 15mm

Model	HDF6015L-05LB	HDF6015L-05MB	HDF6015L-05HB	HDF6015L-12LB	HDF6015L-12MB	HDF6015L-12HB
Frame Size (mm)	60 x 15	60 x 15	60 x 15	60 x 15	60 x 15	60 x 15
Rated Vol (VDC)	5	5	5	12	12	12
Operating Volt (VDC)	4.25-5.75	4.25-5.75	4.25-5.75	10.2-13.8	10.2-13.8	10.2-13.8
Rated Current (mA)	175	270	360	75	110	135
Rated Input (W)	0.88	1.35	1.8	0.9	1.32	1.62
Max. Air Flow (CFM)	11	14	18	11	16	18
Max. Static Pres. (Inch Aq)	0.06	0.1	0.16	0.06	0.12	0.16
Noise (1m) (dB(A))	21	25	32	21	28	32
Speed (rpm)	2800	3350	4400	2800	3700	4400
Weight (Oz)	1.5	1.5	1.5	1.5	1.5	1.5

