

EBS WM 575P3

Compact Wallmount system



FEATURES

- ▶ Socket 478 for Intel® Pentium® 4/P4-M/Celeron® processor up to 2.8GHz+ with 400/533 MHz FSB
- ▶ 184-pin DIMM x 2, support Max. 2GB DDR 266/333 Memory
- ▶ 10/100 Fast Ethernet LAN port x 3
- ▶ Serial port x 3, USB 2.0 x 2
- ▶ 3.5" HDD Drive Bay x 2
- ▶ 5.25" Drive Bay x 1

SPECIFICATION

Construction

- . Heavy-duty steel chassis

Dimension

- . 127mm(W)x228.6mm(H)x355.6mm(D)
- . 5"(W)x9"(H)x14"(D)

Color

- . RAL 7035

Ethernet

- . LAN chip: Intel 82551QM (PRO/100 Network Connection) x 2 and Intel 82562EM x 1
- . 10/100 Fast Ethernet LAN port x 3

Main Board

- . EBC 575-P
- . CPU: Support Intel Pentium 4/P4-M/Celeron processor up to 2.8GHz with 400/533 MHz FSB and 512KB L2 Cache
- . Chipsets: Intel845GV + ICH4

Device

- . Compact Flash card socket x 1
- . 184-pin DIMM x 2, support unbuffered non-ECC DDR 266/333 up to 2GB
- . 5.25" Drive Bay x 1 (Max. Depth: 17cm)
- . 3.5" internal Hard Disk Drive Bay x 2

I/O Ports

- . 10/100 Fast Ethernet LAN port x 3
- . VGA port x 1
- . Serial port x 2
- . USB2.0 port x 2
- . Parallel port x 1
- . PS/2 Keyboard & Mouse connector x 1

Expansion

- . 32bit PCI expansion slot x 3 (via EBK PCIR3)
- . PCI slot 1: support PCI Add-On card up to 235mm in length
- . PCI slot 2&3: support PCI Add-On card up to 135mm in length

System Control and Indicator

- . Power on/off LED x 1
- . HDD Access LED x 1
- . Power on/off switch at front

Power supply

- . 180W power supply inside

Environment

- . Operating temperatures: 0°C to 40°C
- . Storage temperatures: -20°C to 80°C
- . Relative humidity: 10% to 90% (Non-condensing)

Certification:

- . CE
- . FCC

Ordering Information

Model Name	MainBoard	Chassis	AC Adaptor
EBS WM575P3	EBC575-P	EBE WM	180W