

PAC-70AH PAC-75H

7-slot Half-size Industrial PC Chassis



PAC-70AH

SPECIFICATIONS

- ◆ Drive Bays : 1 x 3.5" FDD, 1 x 3.5" HDD
- ◆ One hot-removable 8cm cooling fan with filter
- ◆ Designed with fan fault detecting system
- ◆ Supports backplane : BP-7S, IP-7S
- ◆ Supports power supply : PS/2 size AT/ATX power supply
- ◆ Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Color : White (PANTONE 413C)
- ◆ Dimensions : 321(W) x 175.5(H) x 280.6(D)mm; (12.6"x6.9"x11")
- ◆ Net/GW : 7/10 (kg)

ORDERING INFORMATION

- **PAC-70AHW/ACE-920A:**
7-slot compact chassis with ACE-920A power supply



PAC-75H

SPECIFICATIONS

- ◆ Front panel with lockable door to protecting the system safety
- ◆ Drive Bays : 1 x 3.5" FDD, 1 x 5.25" Drive, 1 x 3.5" HDD
- ◆ One hot-removable 8cm cooling fan with filter
- ◆ Designed with fan fault detecting system
- ◆ Supports backplane : BP-7S or IP-7S
- ◆ Supports power supply : ACE-890 series power supply
- ◆ Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Color : White (PANTONE 413C)
- ◆ Dimensions : 321(W) x 175.5(H) x 280.6(D)mm; (12.6"x6.9"x11")
- ◆ Net/GW : 7/9 (kg)

ORDERING INFORMATION

- **PAC-75HW/ACE-890A:**
7-slot compact chassis with ACE-890A power supply

PR103/105 PAC-50/51/52

3, 5-slot Half-size Industrial PC Chassis

3, 4, 6-slot Half-size Industrial PC Chassis

PR-103

PR-105



SPECIFICATIONS

- ◆ Drive Bays : PR-103 : 1 x 3.5" FDD
PR-105 : 2 x 3.5" FDD
- ◆ One 8cm cooling fan with removable filter
- ◆ Supports backplane : PR-103 : BP-3S, IP-3S
PR-105 : BP-5S, IP-5S
- ◆ Supports power supply : ACE-870 series or ACE-865V
- ◆ Ship with a mounting kit for Rack mounting solution
- ◆ Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Colors : White (PANTONE 413C)
- ◆ Dimensions :
PR-103 : 266(W) x 88(H) x 254(D)mm; (10.5" x 3.5" x 10")
PR-105 : 266(W) x 132(H) x 254(D)mm; (10.5" x 5.2" x 10")
- ◆ Net/GW (kg) : 3/6(PR-103), 4/6(PR-105)

ORDERING INFORMATION


- **PR-103W/ACE-P** : 3-slot compact chassis with ACE- P power supply
 - **PR-105W/ACE-P** : 5-slot compact chassis with ACE- P power supply
- P Power Supply

Standard Version :

- **PR-103W/ACE-870A:**
3-slot compact chassis with ACE-870A power supply
- **PR-105W/ACE-870A:**
5-slot compact chassis with ACE-870A power supply



PAC-50



PAC-51



PAC-52

SPECIFICATIONS

- ◆ Supports backplane :
– PAC-50 : IP-3S, BP-3S, IP-3S2
– PAC-51 : IP-4S, BP-4S, IP-4S2
– PAC-52 : IP-6S, BP-6S
- ◆ Supports max. card length : 190mm
- ◆ Five DC input terminal block for power supply connection
- ◆ Convenient FDD, HDD & parallel port cables for external connection
- ◆ Vibration :
– 5~17Hz, 0.1" double amplitude displacement
– 17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock :
10G acceleration peak to peak (11ms)
- ◆ Color :
Industrial Green (PANTONE 417C)
- ◆ Dimensions :
– PAC-50 :
91(W) x 146.7(H) x 218(D)mm;
(3.6" x 5.7" x 8.6")
– PAC-51 :
114(W) x 146.7(H) x 218(D)mm;
(4.5" x 5.7" x 8.6")
– PAC-52 :
152(W) x 146.7(H) x 218(D)mm;
(6" x 5.7" x 8.6")
- ◆ Net/GW (kg) : 2/3 (PAC-50/51/52)

ORDERING INFORMATION

- **PAC-50G/B** : 3-slot compact chassis with B backplane
 - **PAC-51G/B** : 4-slot compact chassis with B backplane
 - **PAC-52G/B** : 6-slot compact chassis with B backplane
- B Backplane
(Please select specified backplane for each PAC-50/51/52 chassis)