




CPU Cards

Intel® 2nd Generation Core™ i7/i5/i3-Based

LGA1155 PICMG 1.3 Intel® 2nd Generation Core™ i7/i5/i3/Pentium® processor Full-Size CPU Card w/ Intel® Q67 PCH

- 1 Motherboards
- 2 Disk-Size SBDS
- 3 CPU Modules
- 4 PC/104 Plus
- 5 CPU Card
- 6 Embedded Systems
- 7 Network Security Appliance

IB960



Features

- 2nd Generation Intel® Core™ i7 / i5 / i3 / Pentium® QC/DC processors, up to 3.4GHz
- 2x DDR3 DIMM, Max. 8GB
- Intel® processor integrated graphics device, Gfx Gen 5.7, supports CRT, DVI-D and LVDS
- Dual Intel® Gigabit LAN
- 9x USB, 2x COM, 4x SATA II, 2x SATA III
- Watchdog timer, Digital I/O, PCI-E to PATA
- 1x Mini PCI-E

System

CPU Socket	LGA1155 for Intel® 2nd Generation Core™ i7 / i5 / i3 / Pentium® QC/ DC processors, up to 3.4GHz
System Memory	2x DDR3 DIMM, Max. 8GB (Non-ECC)
System Chipset	Intel® Q67 PCH
BIOS	AMI
Watchdog Timer	256 levels
SSD	N/A
H/W Monitor	Yes
Expansion Slot	1x Mini PCI-E

Graphics

VGA Controller	Intel® 2nd Generation Core™ i7 / i5 / i3 / Pentium® QC/ DC processor integrated Gfx Gen 5.7
VGA Memory	Max. shared memory – 1024MB
LCD Interface	Supports CRT, DVI-D and 24-bit dual channel LVDS interface

LAN

LAN Controller	Intel® 82579V Gigabit LAN PHY Intel® 82583V PCI-E Gigabit LAN
Connector	RJ-45 on board

Multi I/O

I/O Chipset	Winbond W83627DHG-P 1x KB, 1x mouse, 1x RS232, 1x RS232/422/485, 4x SATA II, 2x SATA III, 1x LPT
USB	1 port on board Pin headers for 8 ports (USB 2.0)
Audio	Intel® Q67 PCH built-in HD audio controller + Realtek ALC662 codec for 5.1CH
Others	Digital I/O (4-in/4-out), IrDA, RAID

Mechanical and Environmental

Dimensions	338mm x 122mm (13.31" x 4.8")
Max. Power Requirement	TBC
Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	10%~90% (non-condensing)

Ordering Information

IB960F	LGA1155 PICMG1.3 Q67 Full-Size CPU Card w/ VGA, DVI-D, 24-bit LVDS, dual Gigabit LAN
--------	--

Remarks:

* Specifications are subject to change without prior notice.