




IC Socket Stamped Dual Wipe

ASSMANN
ELECTRONICS, INC., U.S.A.



FEATURES AND OPTIONS

- Available in sizes 6 through 64
- Skinny dip versions available on 24 and 28 pin sockets
- Closed bottom style for anti-wicking
- Tin plated contacts
- Straight or retention leg option available

SPECIFICATIONS

MATERIALS

Contact: Phosphor Bronze
Insulator: PBT & 30% Glass Fiber (UL 94V-O)

ELECTRICAL

Current rating: 1A
Voltage: AC 500V for 1 minute
Operating temperature range: -55°C to +150°C
Contact resistance: 30mΩmax, at DC 100mA
Insulator resistance: 1000MΩmin. at DC 500V

DIMENSIONS

# of Pins	A	B	C	D
6	7.62/3	7.62/3	10.16/4	7.62/3
8	10.16/4	7.62/3	10.16/4	7.62/3
14	17.78/7	15.24/6	10.16/4	7.62/3
16	20.32/8	17.78/7	10.16/4	7.62/3
18	22.86/9	20.32/8	10.16/4	7.62/3
20	25.40/1.0	22.86/9	10.16/4	7.62/3
22	27.94/1.1	25.40/1.0	10.16/4	7.62/3
24	30.48/1.2	27.94/1.1	10.16/4	7.62/3
24	30.48/1.2	27.94/1.1	17.78/7	15.24/6
28	35.56/1.4	33.02/1.3	10.16/4	7.62/3
28	35.56/1.4	33.02/1.3	17.78/7	15.24/6
32	40.54/1.6	38.10/1.5	17.78/7	15.24/6
40	50.80/2.0	48.26/1.9	17.78/7	15.24/6
48	60.80/2.4	58.42/2.3	17.78/7	15.24/6
64	81.24/3.2	78.43/3.1	25.99/1.02	22.86/9

HOW TO ORDER

AXX-LC-TX

- T = Straight solder tail
- R = Retentive leg version
- Use 7 to indicate skinny dip (.300)
- C = Tin
- CG = Gold
- XX = Number of contacts